

ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U.

www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category
EC	Efficiency category
VSD	Variable Speed Drive
SR	Specific ratio

[m³/h]	Flow rate
[Pa]	Static pressure / Total pressure
[RPM]	Speed

η_e [%]	Efficiency
N	Efficiency grade
[kW]	Input power

Model	MC	EC	VSD	SR	η _e [%]	N	[kW]	[m ³ /h]	[Pa]	[RPM]
NEOSILENT 100										ErP Exclude. Pe < 125 W
NEOSILENT 125										ErP Exclude. Pe < 125 W
NEOSILENT 150										ErP Exclude. Pe < 125 W
NEOSILENT 200										ErP Exclude. Pe < 125 W
NEOSILENT 200 3V										ErP Exclude. Pe < 125 W
NEOSILENT 250	A	Static	VSD not necessary	1.00	30.9	49.4	0.174	803	236	2505
NEOSILENT 315	A	Static	VSD not necessary	1.00	32.4	54.9	0.317	1112	326	2320