

ECODESIGN INFORMATION

www.sodeca.com

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type

b) fan efficiency [%]

c) VSD assumed in data

d) Measurement category
- e) Efficiency category

f) N fan

g1) Pe [kW]

g2) qv [m³/h]
- g3) Δp [Pa]

h1) dual use fan

h2) reversible fan

h3) low noise fan
- i) DC voltage lower than 100 V

k) σBEP

l) fan speed [rpm]

m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
WALL/AXIAL-A/B-40-4T	Axial fan	33.7	VSD not necessary	A	Static	50.4	0.259	3702	84	No	No	No	No	0.00	1350	1.00
WALL/AXIAL-A/B-45-4T	Axial fan	46.7	VSD not necessary	C	Static	62.3	0.330	4318	128	No	No	No	No	0.00	1370	1.00
WALL/AXIAL-A/B-50-4T	Axial fan	42.0	VSD not necessary	C	Static	55.6	0.498	5341	141	No	No	No	No	0.00	1420	1.00
WALL/AXIAL-A/B-56-4T IE3	Axial fan	56.8	VSD not necessary	D	Total	67.2	1.022	11151	187	No	No	No	No	0.00	1455	1.00
WALL/AXIAL-A/B-56-6T	Axial fan	35.7	VSD not necessary	A	Static	51.4	0.322	5123	80	No	No	No	No	0.00	900	1.00
WALL/AXIAL-A-63-4T IE3	Axial fan	41.7	VSD not necessary	C	Static	51.7	1.118	9320	180	No	No	No	No	0.00	1455	1.00
WALL/AXIAL-A-63-6T	Axial fan	36.8	VSD not necessary	A	Static	50.7	0.479	6809	93	No	No	No	No	0.00	900	1.00
WALL/AXIAL-A-71-4T IE3	Axial fan	44.8	VSD not necessary	C	Static	53.0	1.682	13653	199	No	No	No	No	0.00	1440	1.00
WALL/AXIAL-A-71-6T IE3	Axial fan	62.8	VSD not necessary	D	Total	74.9	0.704	15863	100	No	No	No	No	0.00	940	1.00
WALL/AXIAL-B-63-4T IE3	Axial fan	41.7	VSD not necessary	C	Static	51.7	1.118	9320	180	No	No	No	No	0.00	1455	1.00
WALL/AXIAL-B-63-6T	Axial fan	36.8	VSD not necessary	A	Static	50.7	0.479	6809	93	No	No	No	No	0.00	900	1.00
WALL/AXIAL-B-71-4T IE3	Axial fan	44.8	VSD not necessary	C	Static	53.0	1.682	13653	199	No	No	No	No	0.00	1440	1.00
WALL/AXIAL-B-71-6T IE3	Axial fan	62.8	VSD not necessary	D	Total	74.9	0.704	15863	100	No	No	No	No	0.00	940	1.00