ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

a) fan type
b) fan efficiency [%]
c) VSD assumed in data
d) Measurement category
e) Efficiency category
f) N fan
g1) Pe [kW]
g2) qv [m³/h]
g3) Δp [Pa]
h1) dual use fan
h2) reversible fan
h3) low noise fan
i) DC voltage lower than 100 V
k) σBEP
l) fan speed [rpm]
m) specific ratio
j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CBD/EC-1919-4M-1/5 IE4	*ErP Exclude. Pe < 125 W*															
CBD/EC-1919-6M-1/10 IE4	*ErP Exclude. Pe < 125 W*															
CBD/EC-2525-4M-1/2 IE4	forward curved centrifugal fan	51.1	VSD built-in to the fan	C	Static	66.6	0.340	1750	314	No	No	No	No	0.00	1400	1.00
CBD/EC-2525-4M-3/4 IE4	forward curved centrifugal fan	49.0	VSD built-in to the fan	C	Static	64.4	0.342	1738	305	No	No	No	No	0.00	1400	1.00
CBD/EC-2525-4M-1 IE4	forward curved centrifugal fan	50.7	VSD built-in to the fan	C	Static	67.1	0.274	1402	309	No	No	No	No	0.00	1400	1.00
CBD/EC-2525-6M-1/3 IE4	*ErP Exclude. Pe < 125 W*															
CBD/EC-2828-4M-1 IE4	forward curved centrifugal fan	52.2	VSD built-in to the fan	C	Static	64.9	0.621	2438	434	No	No	No	No	0.00	1400	1.00
CBD/EC-2828-4M-2 IE4	forward curved centrifugal fan	46.7	VSD built-in to the fan	C	Static	58.9	0.693	2597	409	No	No	No	No	0.00	1400	1.00
CBD/EC-2828-6M-1/3 IE4	forward curved centrifugal fan	52.4	VSD built-in to the fan	C	Static	70.9	0.172	1608	169	No	No	No	No	0.00	900	1.00
CBD/EC-3333-6M-1 IE4	forward curved centrifugal fan	42.7	VSD built-in to the fan	C	Static	56.3	0.503	2648	262	No	No	No	No	0.00	900	1.00