

ECODESIGN INFORMATION

According to Regulation EU No 2024/1834 of the European Commission, implementing Directive 2009/125/CE of European Parliament

SODECA, S.L.U.

- a) fan type
b) fan efficiency [%]
c) VSD assumed in data
d) Measurement category
- e) Efficiency category
f) N fan
g1) Pe [kW]
g2) qv [m³/h]
- g3) Δp [Pa]
h1) dual use fan
h2) reversible fan
h3) low noise fan
- i) DC voltage lower than 100 V
k) σBEP
l) fan speed [rpm]
m) specific ratio
- j) p) q) significant elements, disassembly and recycling info on product manual

Model	a)	b)	c)	d)	e)	f)	g1)	g2)	g3)	h1)	h2)	h3)	i)	k)	l)	m)
CBD/EC-1919-4M-1/5 IE4	ErP Exclude. Pe < 125 W															
CBD/EC-1919-6M-1/10 IE4	ErP Exclude. Pe < 125 W															
CBD/EC-2525-4M-1/2 IE4	forward curved centrifugal fan	51.1	VSD built-in to the fan	C	Static	66.6	0.340	1750	314	No	No	No	No	0.00	1400	1.00
CBD/EC-2525-4M-3/4 IE4	forward curved centrifugal fan	49.0	VSD built-in to the fan	C	Static	64.4	0.342	1738	305	No	No	No	No	0.00	1400	1.00
CBD/EC-2525-4M-1 IE4	forward curved centrifugal fan	50.7	VSD built-in to the fan	C	Static	67.1	0.274	1402	309	No	No	No	No	0.00	1400	1.00
CBD/EC-2525-6M-1/3 IE4	ErP Exclude. Pe < 125 W															
CBD/EC-2828-4M-1 IE4	forward curved centrifugal fan	52.2	VSD built-in to the fan	C	Static	64.9	0.621	2438	434	No	No	No	No	0.00	1400	1.00
CBD/EC-2828-4M-2 IE4	forward curved centrifugal fan	46.7	VSD built-in to the fan	C	Static	58.9	0.693	2597	409	No	No	No	No	0.00	1400	1.00
CBD/EC-2828-6M-1/3 IE4	forward curved centrifugal fan	52.4	VSD built-in to the fan	C	Static	70.9	0.172	1608	169	No	No	No	No	0.00	900	1.00
CBD/EC-3333-6M-1 IE4	forward curved centrifugal fan	42.7	VSD built-in to the fan	C	Static	56.3	0.503	2648	262	No	No	No	No	0.00	900	1.00